



B SERIES AUTO SHRINK SLEEVE LABELLER



Features & Advantages

- 1. Drive and cutter motors use Yaskawa system for better stability and durability.
- 2. Bottle Diameter: 135 220mm.
- 3. Adopts Dual drive system for constant sleeve insertion.
- 4. Cutter design uses gear type for longer life span.
- 5. Drive and mandrel supports are interlink designed to accurately hold mandrel into place.
- 6. Sleeve feeding roller uses convex design for faster sleeve installation.
- 7. HMI adopts 9.7" screen for easier and convenient usage.
- 8. Sensors use Sick brand for constant and accurate detection.



Packaging Types



Sealing Type





Bottle Type Labeling Type







(The above images protected by copyright. Any use without permission from DASE-SING is stricly prohibited.)

Product Characteristics

- 1. Adopts Ethernet communication interface for online production integration.
- 2. Safety guards and color touch panel control system ensure unit is user friendly.
- 3. Specially designed cutter plate does not need changing within rated specifications. If necessary, changes can be accomplished in only three minutes.
- 4. Forceful insertion designs could lower producing cost for you.
- 5. Integrated adjustment design for the entire transmission maximizes versatility for accommodating different label specifications.
- 6. Accommodates film paper core size from 5"-10" with variable adjustments.
- 7. PLC(Programmable Logic Control) for increased accuracy and speed over conventional controls.

MODEL	DSK-2B
Power source	3P; 220V, 380V, 415V, 460V
Production speed	Max: 150bpm per 150mm label length. The longer the length of the label, the slower the speed.
Machine Dimension	1100mm*1180 mm*2000mm(L*W*H) (Based on 1200mm conveyor height from ground to top chain)
Power Consumption	10KW
Cutter Plate Dimensions	[Ø135mm-Ø165mm],[Ø165mm~195mm],[Ø195mm~220mm]
Bottle Diameter	Ø135mm~Ø220mm(Based on customer provided bottle specs)
Label Material	PVC \ PET \ OPS
Label Thickness	PVC: 0.04mm~0.05mm; PET: 0.04mm~0.05mm; OPS:0.04mm-0.05mm
Label Length	50mm-240mm



www.dasesing.com dasesing@dasesing.com



DASE-SING GROUP

DASE-SING PACKAGING TECHNOLOGY CO., LTD.

Head Office /

(A) +886.5.289.1306 (F) +886.5.289.1212

O No.7, Zhongzhuang, Shuishang Township, Chiayi Country 60857, Taiwan

Hsinchu Office/

(2) +886.3.568.6478

+886.3.568.6375

O No.465-1, Puding, Lin 18, Puhe Village, Xinfeng Township, Hsinchu Country 30446, Taiwan

SHANGHAI DASE-SING PACKAGING TECHNOLOGY CO.,LTD.

Shanghai Office /

+86.21.3365.8333

+86.21.3365.8732

No.1189, Fengpu Dadau, Nanqiao Town, Fengxian, China. (Postal code: 201400)